



**LIFE-TIME
WARRANTY**

Marquis[®] Protector Lockers

The most durable and quiet corridor locker in the market is constructed with our fully-framed all-welded Hollow-T framing system.

If you're looking for corridor lockers to last the life of your facility, our Marquis Protector is your best choice and is backed up in writing by our lifetime warranty.

Marquis Protector Locker Features:

- Fully-framed all-welded construction
- 14 gauge plain doors
- 18 gauge full-height door stiffener for all doors
- New deep-drawn seamless stainless steel recessed handle for all doors
- Single-point maintenance-free quiet latching system
- 11 gauge MIG welded latch with pry resistant lug
- Heavy-duty 13 gauge 7-knuckle 3-1/2" hinges
 - 3-hinges per opening 48" high and higher
 - 2-hinges per opening 20" high thru 36" high
- 18 gauge fully-framed solid sides
- 16 gauge continuous top
- 16 gauge galvanized hat shelf for single tier openings 60" and 72" high
- 16 gauge galvanized bottom and intermediate shelves
- 18 gauge solid back

Note: Security-Plus, louvered and diamond perforated door styles are optional for all Marquis Protector lockers.

See page 10 for standard sizes



FULLY-FRAMED ALL-WELDED
MARQUIS[®] PROTECTOR CORRIDOR LOCKERS



The Industry's Toughest Locker

FULLY-FRAMED ALL-WELDED
MARQUIS® PROTECTOR CORRIDOR LOCKERS



STANDARD

Deep-drawn stainless steel recessed handle with single-point latching



STANDARD

11 gauge single-point latch with pry resistant lug is MIG welded to Hollow-T frame



STANDARD

Our heavy-duty 13 gauge 7-knuckle 3-1/2" hinge vs. common 2" K.D. locker style hinge



STANDARD

Marquis Protector lockers include a 3" wide 18 gauge full height door stiffener spot welded to the inner door face and MIG welded to the hinge side as well as to the top and bottom door flanges providing a rigid torque-free door. A 1-1/2" wide stiffener will be furnished for 9" wide Marquis doors.

MARQUIS PROTECTOR SPECIFICATIONS

General: Lockers shall be "Superior Fully-Framed All-Welded Marquis Protector Corridor Lockers" as manufactured by List Industries Inc. or approved equal. All lockers shall be factory-assembled, of all MIG welded construction, in multiple column units to meet job conditions. Assembly of locker bodies by means of bolts, screws, or rivets will not be permitted. Welding of knockdown locker construction is not acceptable. Grind exposed welds and metal edges flush and make safe to touch.

Finishing: All locker parts to be cleaned and coated after fabrication with a seven stage zinc/iron phosphate solution to inhibit corrosion, followed by a coat of high grade enamel electrostatically sprayed and baked at 325 degrees Fahrenheit for a minimum of 30 minutes to provide a tough durable finish. Color to be selected from manufacturer's standard list of colors. Two-tone color combination shall be at no additional cost with the locker body, frame and trim chosen from one color and the doors may be one of any other color chosen from manufacturer's standard selection.

Frame / Vertical Side panels: Shall be of 18 gauge solid cold rolled sheet steel framed by 16 gauge Hollow-T tubular sections and channel frame members designed to enclose all four edges of the side panel with the entire assembly MIG welded to form a rigid frame for each locker. The channel frame members are welded to the front and rear vertical frame members to create and anchor bearing surface of 1-1/4 inches wide x the depth of the locker at each side panel.

Integral Frame Locker base: 14 gauge formed structural channels are MIG welded to the front and rear vertical side panel frame members to allow placement of locker bottom a minimum 2-3/4" above floor level. Locker bottom shelf located less than 2" above floor level will not be acceptable.

Marquis Protector Wardrobe And Gym Doors: Outer door to be fabricated from single sheet prime 14 gauge with single bends at top and bottom and double bends at the sides with a 3" wide (1-1/2" for 9" wide doors) 18 gauge full height channel door stiffener MIG welded to the hinge side of the door as well as to the top and bottom door return bends and spot welded to the inside of door face to form a rigid torque-free box reinforcement for the door. Doors to be solid (non-perforated) with ventilating perforations in the top and bottom door flanges.

Marquis Seamless Drawn Stainless Steel Recessed Locker Handle: All locker doors shall have a seamless drawn stainless steel recessed handle shaped to receive a padlock or built-in combination lock. The recess pan shall be deep enough to have the lock be completely flush with the outer door face. The pull handle shall be drawn into the left side of the handle for easy opening of the locker door.

Marquis Latch Assembly: Shall be single point rigid non-moving positive latch by means of a heavy gage (minimum 11 gage) latch securely welded to the framed vertical divider. The latch assembly must be made of a single piece of steel and have a padlock loop that inserts through the recess pan. The latch must be able to accept either a padlock or built-in combination lock. A pry resistant lug which inserts into the door shall be an integral part of the 11 gage latch. Rubber bumpers shall be securely attached to the door strike.

Door Hinges: Hinges shall not be less than 3-1/2" long 13 gauge seven knuckle pin type, securely riveted to frame and welded to the door. Doors are to be secured to frame with a minimum of two tamper resistant rivets per hinge. Provide 3 hinges for doors 48" and higher and 2 for doors shorter than 48". All doors shall be right hand side hinged.

Flat Tops: Shall be formed of one piece of 16 gauge cold rolled sheet steel and shall be an integral part MIG welded to each vertical side panel frame member and be continuous to cover the full width of a multiple framed locker unit.

Hat Shelves, Intermediate Shelves And Bottoms: Shall be 16 gauge galvaneal sheet steel, have double bends at front and shall engage slots in the Hollow-T vertical frame members at all four corners and be securely welded to the frame and side. Locker bottom shelf located less than 2" above floor level will not be acceptable.

Backs: Shall be 18 gauge cold rolled sheet steel, be continuous to cover a multiple framed unit and be welded to each vertical side panel frame member.

Locks (If Required): Shall be master keyed to one system for the entire project. (See lock use chart for suggested lock application).

Equipment: Openings 60" and 72" shall include one galvaneal hat shelf. One double hook and two single hooks are standard with the following exceptions:

- Openings 20" and 24" high:** One double hook only at 12" wide and wider.
- Openings 9" wide:** Two single hooks only.
- Openings 18" high and under:** No hooks.

Lifetime Warranty: Superior fully-framed all-welded lockers are covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section for the lifetime of the facility.