



Marquis® Student KD Lockers



First introduced in 1983, Superior Marquis Student KD lockers are the most specified single-point lockers in the marketplace.

Designed with superior features usually reserved for heavy-duty athletic lockers, our fifth generation Marquis Student locker is an engineering achievement.

Demand the best, demand Superior, demand Marquis Student lockers!

Note: See page 26 for standard wardrobe locker sizes

Marquis Student KD Locker Features

- Knock-Down (KD) construction
- 14 gauge plain doors
- 18 gauge full-height door stiffener
- 24 gauge solid body components
- Heavy-duty 13 gauge 7-knuckle 3-1/2" hinges
 - 3-hinges for openings 48" high and higher
 - 2-hinges for openings 20" thru 36" high
- Continuous vertical door strike at both hinge and latch side
- All production KD lockers are supplied without legs unless otherwise specified
- 16 gauge horizontal frame cross member between doors of double and triple tier wardrobe lockers
- Deep drawn seamless stainless steel recessed handle
- Single-point maintenance-free quiet latching system
- 11 gauge MIG welded latch with pry resistant lug
- 24 gauge hat shelf for single tier openings 60" and 72" high
- Hooks
 - 3-single hooks and 1-double hook is standard.
 - 1-double hook only for triple tier 12" wide and wider
 - 2-single hooks only for all 9" wide

Notes:

- Security-Plus, louvered and diamond perforated door styles are optional for all Marquis Student lockers
- Optional Horizontal Frame Stiffener (HSA) is recommended for openings 30" and higher to reinforce the frame and single-point latch when a built-in lock is used.
- **MAX option upgrades all components to 16 gauge with 18 gauge back.**

America's Original Single-Point Locker



STANDARD

Deep-drawn stainless steel recessed handle with single-point latching



STANDARD

11 gauge single-point latch with pry resistant lug is MIG welded to frame



STANDARD

Our heavy-duty 13 gauge 7-knuckle 3-1/2" hinge vs. common 2" K.D. locker style hinge



STANDARD

Marquis Student Lockers include a 3" wide 18 gauge full height door stiffener spot welded to the inner door face and MIG welded to the hinge side as well as to the top and bottom door flanges providing a rigid torque-free door. A 1-1/2" wide stiffener will be furnished for 9" wide Marquis doors.

MARQUIS STUDENT SPECIFICATIONS

General: Lockers shall be "Superior Marquis Student KD Lockers" as manufactured by List Industries Inc. or approved equal. Fabricate lockers square, rigid and without warp, with metal faces flat and free from dents or distortion. Make all exposed metal edges safe to touch. Weld frame members together to form rigid, one-piece structure. Weld, bolt, or rivet other joints and connections as standard with manufacturer. Grind exposed welds flush. Do not expose bolts or rivet heads on fronts of locker doors or frames except for fastening of number plates and recessed handle.

Finishing: All locker parts to be cleaned and coated after fabrication with a seven stage zinc/iron phosphate solution to inhibit corrosion, followed by a coat of high grade enamel electrostatically sprayed and baked at 325 degrees Fahrenheit for a minimum of 30 minutes to provide a tough durable finish. Color to be selected from manufacturer's standard list of colors. Interior components to be painted #729 Parchment. Two-tone color combination shall be at no additional cost with the locker frame and trim chosen from one color and the doors may be one of any other color chosen from manufacturer's standard selection.

Frame: Fabricate of 16 gauge (minimum) channels, with integral continuous door stop/strike formed on both latch and hinge side vertical members. Cross frame members of 16 gauge channel shapes, including intermediate cross frame members on double and triple tier (frames with doors over 18" high) lockers shall be securely welded to the vertical framing members to ensure rigidity. Rubber bumpers shall be provided to cushion door closing.

Marquis Student Wardrobe Doors: Doors 20" high and over to be fabricated from single sheet prime 14 gauge with single bends at top and bottom and double bends at the sides. Doors shall include a 3" wide (1-1/2" for 9" wide doors) 18 gauge full height channel door stiffener MIG welded to the hinge side of the door as well as to the top and bottom door return bends and spot welded to the inside of door face to form a rigid torque-free box reinforcement for the door. Doors shall be plain (non-louvered). Wardrobe doors shall include ventilating perforations in the top and bottom door flanges.

Marquis Seamless Drawn Locker Handle: All wardrobe doors 20" high and over shall have a seamless drawn stainless steel recessed handle shaped to receive a padlock or built-in combination lock. The recessed handle shall be deep enough to have the lock be completely flush with the outer door face.

Marquis Latch Assembly: Shall be single point rigid non-moving positive latch by means of a heavy 11 gauge (minimum) latch securely welded to the 16 gauge vertical frame member at both the continuous door strike as well as the area where the frame is fastened to the side panel to prevent the latch and frame from twisting. The latch assembly must be made of a single piece of steel and have a padlock loop that inserts through the recess pan. The latch must be able to accept either a padlock or built-in combination lock. A pry resistant lug which inserts into the door shall be an integral part of the 11 gauge latch. A rubber bumper shall be securely attached to the latch.

Door Hinges: Shall not be less than 3-1/2" long 13 gauge seven knuckle pin type, securely welded to frame and riveted to the door. Provide 3 hinges for doors 48" and higher and 2 for doors under 48" high. All doors to be right hand, side hinged.

Body: Fabricate back and sides of 24 gauge (minimum) sheet steel, with double flanged connections extending full height. Form top, bottom and intermediate tier dividers of 24 gauge (minimum) sheet steel with single return bends at all sides. Bolt top and bottom as well as horizontal tier dividers of wardrobe openings to front horizontal frame members at not less than two places in addition to side panels. Form hat shelves at 60" and 72" high single tier lockers of 24 gauge (minimum) sheet steel with single bends at sides and back and a double bend at front.

Locks (If Required): Shall be master keyed to one system for the entire project. (See lock use chart for suggested lock application).

Equipment: Openings 60" and 72" shall include one hat shelf. One double hook and three single hooks are standard with the following exceptions:

Openings 20" and 24" high: One double hook only at 12" wide and wider.

Openings 9" wide: Two single hooks only.

Two-Year Warranty: Superior KD lockers are covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section for a period of two years.

MARQUIS STUDENT
KD CORRIDOR LOCKERS